



2017

AC A	200/600A $\pm 1.5\% \text{rdg} \pm 4 \text{dgt}$ [50/60Hz] (200A) $\pm 1\% \text{rdg} \pm 3 \text{dgt}$ [50/60Hz] (600A) $\pm 2\% \text{rdg} \pm 5 \text{dgt}$ [45Hz~1kHz]
AC V	200/600V $\pm 1\% \text{rdg} \pm 2 \text{dgt}$ [50/60Hz] $\pm 1.5\% \text{rdg} \pm 4 \text{dgt}$ [45Hz~1kHz]
Ω	200 Ω $\pm 1.2\% \text{rdg} \pm 2 \text{dgt}$
Continuity buzzer	buzzer sounds below $30 \pm 20 \Omega$
Conductor Size	$\varnothing 33 \text{mm}$ max.
Safety Standard	IEC 61010-1 CAT.III 600V Pollution Degree 2 IEC 61010-2-031
Frequency Response	45Hz~1kHz
Withstand Voltage	5550V AC for 1 minute
Power Source	6F22 (9V) \times 1
Dimensions	208(L) \times 91(W) \times 40(D)mm
Weight	400g approx.
Accessories	7066A (Test leads) 9079 (Carrying case) 6F22 \times 1 Instruction Manual
Optional	8008 (Multi-Tran)