



# 2009

	400.0/2000A $\pm 1.3\% \text{rdg} \pm 3 \text{dgt}$ (0~400.0A, 150~1700A) (45~66Hz) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt}$ (0~400.0A, 150~1700A) (20Hz~1kHz) $\pm 2.3\% \text{rdg} \pm 3 \text{dgt}$ (1701~2000A) (45~66Hz)
DC A	400.0/2000A $\pm 1.3\% \text{rdg} \pm 2 \text{dgt}$
AC V	40.00/400.0/750V $\pm 1.0\% \text{rdg} \pm 3 \text{dgt}$ (45~66Hz) $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$ (20Hz~1kHz)
DC V	40.00/400.0/1000V $\pm 1.0\% \text{rdg} \pm 2 \text{dgt}$
$\Omega$	400.0/4000 $\Omega$ $\pm 1.5\% \text{rdg} \pm 2 \text{dgt}$ (Electronic protection (no fuse) up to 600V)
Continuity buzzer	Buzzer sounds below 20 $\Omega$
Hz	10.0 ~ 4000Hz $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$ (Input sensitivity Current: more than 40A Voltage: more than 10V)
Output	Recorder : DC400mV against AC/DC400.0A DC200mV against AC/DC2000A
Withstand voltage	6880V AC for 5 seconds
Conductor size	$\text{O}55\text{mm}$ max.
Applicable standards	IEC 61010-1 CAT.IV 600V, CAT.III 1000V Pollution degree 2 IEC 61010-031, IEC 61010-2-032, IEC 61326-1, IEC 61326-2-1
Power Source	R6P (1.5V) $\times$ 2
Dimensions	250(L) $\times$ 105(W) $\times$ 49(D)mm
Weight	Approx. 540g (including batteries)
Accessories	<a href="#">7107A</a> (Test leads), <a href="#">8201</a> (Output plug), 9094 (Carrying case) R6P (AA) (1.5V) $\times$ 2, Instruction Manual
Optional	<a href="#">8008</a> (Multi-Tran) (AC only), <a href="#">7256</a> (Output cord)